

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICANT: CHIU, Hsiu-Feng

SERIAL NO.:

FILED: Herewith

TITLE: EVAPORATIVE SCENT BURNER PROVIDED WITH A GYPSUM EVAPORATIVE
BASE

Preliminary Amendment: CLAIM AMENDMENTS

1. (Currently amended) An evaporative scent burner comprising:

a bottle, ~~which is~~ used to accommodate the essential oil, ~~with its~~ having a top
provided with a bottle mouth. ~~And, and~~ a screw thread is mounted at ~~the~~ a periphery of the bottle
mouth;

a gypsum evaporative base, ~~which~~ having a bottom is provided onto the bottle mouth
of ~~above-mentioned~~ said bottle while its a top thereof ~~can be designed with~~ has an enlargement
surface for a larger area of evaporation;

a braided wire, ~~which~~ with a head is connected to the gypsum evaporative base while
the bottom of the braided wire will fall inside the bottle to absorb essential oil. ~~The advantages of~~
~~the present invention include:~~

————— wherein a reinforcement base, ~~which~~ is built-in in the gypsum evaporative base:
~~Constructed and comprised~~ of rigid materials of strong toughness, the reinforcement base is being
provided with a screw notch where a screw thread at the periphery of bottle mouth can be properly
screwed. ~~And, and~~ a punching hole is provided inside the screw notch, where a braided wire can
cross through and the braided wire head can be fastened. ~~Besides, this, wherein said~~ reinforcement

base is available with a ring-type wall to separate braided wire and gypsum evaporative base, with its aim of preventing the gypsum evaporative base from breakdown or strip or leakage.

2. (Original) The evaporative scent burner defined in Claim 1, wherein said convex rib can be separately mounted at the outer flank of the ring-type wall of reinforcement base, thereby fastening securely the gypsum evaporative base.

3. (Currently amended) The evaporative scent burner defined in Claim 1, wherein said bottom of ring-type wall of the reinforcement base can protrude from the gypsum evaporative base: ~~So~~ wherein, when the gypsum evaporative base is installed onto the bottle mouth, the bottom of the ring-type wall of reinforcement base can ~~insert~~ be inserted into the inner wall of the bottle mouth for a desirable fixation.